


50CT 5.2 ϕ × 20


高分断能力瓷保险丝管(延时型)

HIGH BREAKING CAPACITY CERAMIC TUBE FUSE (TIME-LAG)



I-T CHARACTERISTICS CURVE
电流-时间曲线图

1A 2A 3.15A 4A 5A 6.3A 8A 10A 12A 15A



目录编号 CATALOG NO.	额定电流 AMPERE RATING	最大电压降 mv MAX VOLTAGE DROP	认证 APPROVALS						I ² T 参考值 REFERENCE (A ² S)
			CCC	SEMKO	VDE	BSI	UR	KTL	
0200H	200mA							●	
0250H	250mA							●	0.074
0315H	315mA							●	0.12
0400H	400mA							●	0.31
0500H	500mA							●	0.49
0630H	630mA							●	0.78
0800H	800mA							●	1.5
010H	1A	250	●	●	●	●	●	●	2.3
013H	1.25A	250	●	●	●	●	●	●	3.6
016H	1.6A	200	●	●	●	●	●	●	5.9
020H	2A	190	●	●	●	●	●	●	12
025H	2.5A	180	●	●	●	●	●	●	23
032H	3.15A	140	●	●	●	●	●	●	25
040H	4A	100	●	●	●	●	●	●	51
050H	5A	100	●	●	●	●	●	●	80
063H	6.3A	100	●	●	●	●	●	●	135
080H	8A	100						●	205
100H	10A	100						●	352
120H	12A	100						●	408
150H	15A	100						●	860

H DENOTES FOR 250V (H表示250V)

● DENOTES FOR APPROVED (●表示已取得认证)

分断电流:

BREAKING CAPACITY:

1,500 amperes at 250V AC (200mA-15A)

电气特性 ELECTRICAL CHARACTERISTICS:

额定 RATING		熔断时间 BLOWING TIME			
		200mA-800mA	1A-3.15A	3.15A-6.3A	8A-15A
2.1In	Max(最慢)	30min	30min	30min	30min
	Min(最快)	400ms	1sec	1sec	1sec
2.75In	Max(最慢)	80sec	80sec	80sec	80sec
	Min(最快)	20ms	95ms	150ms	150ms
4In	Max(最慢)	5sec	5sec	5sec	5sec
	Min(最快)	5ms	10ms	20ms	20ms
10In	Max(最慢)	100ms	100ms	100ms	120ms