

GKS-480-12 (12V, 40A, 480W)

GKS-480-24 (24V, 20A, 480W)

Features

- Universal AC input/Full range
- Class I power
- Protections : Short circuit /over load
- Cooling by free air convection
- 100% full load burn-in test
- 1 year warranty



Specification

	Model	GKS-480-12	GKS-480-24
Output	DC Voltage	12V	24V
	Rated Current	40A	20A
	Current Range	0-40A	0-20A
	Rated Power	480W	480W
	Ripple & Noise	200mVp-p	300mVp-p
	Voltage ADJ. Range	10.8-13.2V	21.6-26.4V
	Hold Time	10ms/230Vac at full load	
Input	Voltage Range	230Vac ±10%	
	Frequency Range	47~63Hz	
	Efficiency	75% 115Vac	85% 115Vac
	AC current	6A/230Vac	
	Inrush Current	100A/230Vac	
	Leakage Current	<1mA 230Vac	
Pro-tection	Over Load	110%-180% rated output power	
Environment	Working temp.	-10~ +40°C (refer to output derating curve)	
	Working Humidity	20~90%RH non-condensing	
	Storage Temp., Humidity	-20~+85°C, 10-95% RH	
	Temp. Coefficient	±0.03%/°C (0~50°C)	
	Vibration	10~500Hz, 2G 10min./1cycle, period for 60min, each along X, Y, Zaxes	
	Dimension	240x124x64.1	
	Weight	1.3KGS/PC	

Dimension

