

## Full function adjustable waterproof power supply 240W

- Universal AC input
- Built-in power factor correction
- Protections: short circuit/over load/over voltage/over temp
- Cooling by free air convection
- OCP point adjustable through output cable or internal potentiometer
- IP67/65 design for indoor or outdoor installations
- Suitable for LED lighting and moving sign applications
- 3Year warranty



### HLG-240W

Model		HLG-240-12	HLG-240-20	HLG-240-24	HLG-240-36	HLG-240-48
OUTPUT	DC voltage	12V	20V	24V	36V	48V
	Constant current	6~12V	10~20V	12~24V	18~36V	24~48V
	Rated current	16A	12A	10A	6.7A	5A
	Rated power	192W	240W	240W	241.2W	240W
	Ripple&noise	150mvp-p	150mvp-p	150mvp-p	250mvp-p	250mvp-p
	Voltage ADJ range	11.2~12.8V	18.6~21.4V	22.4~25.6V	33.5~38.6V	44.8~51.2V
	Current ADJ range	Can be adjusted by internal potentiometer or through output cable				
INPUT	Voltage range	90~264VAC, 47~63HZ, 127~370VDC				
	AC current	4A/115VAC, 2A/230VAC				
	Power factor	PF>0.95/230VAC, PF>0.98/115VAC(full load)				
	Efficiency	90%	92%	93%	93%	94%
	Inrush current	cold start current 35A/115VAC, 75A/230VAC				
	Leakage current	<0.75mA/240VAC				
PROTECTION	Over current	95%~108%				
	Short circuit	protection type:Constant current limiting,auto-recovery after fault condition is removed				
	Over voltage	14~17V	23~27V	28~34V	41~46V	54~60V
	Over temperature	protection type: Shut down o/p voltage re-power on to recover				
		100°C±10°C (RTH2)				
ENVIRONMENT	Working	-20°C~+60°C, 20%~90%RH				
	Storage temp, humidit	-40°C~+85°C, 10%~95%RH non-condensing				
	Withstand vibration	10~500Hz, 2G 10min/1cycle, period for 60 minutes, each axes				
SAFETY	Withstand voltage	I/P-O/P: 3KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC				
	Isolated resistance	I/P-O/P,I/P-FG,O/P-FG: 100M ohms/500VDC				
STANDARDS	Safety standard	Fit UL1310 CLASS2,TUV EN61347-1,EN61347-2-13, IP65approved				
	EMC standard	Fit EN55015, EN61000-3-2 ClassC(>60%load):EN61000-3-3				
OTHER	Dimension	247*69*39mm (L*W*H)				
	Weight/packing	1.3kg/20pcs/27kg/0.033m³/1.07CUFT				
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.					
	2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.					
	3. Tolerance : includes set up tolerance, line regulation and load regulation.					