



COTCO LUMINANT DEVICE (HUIZHOU) LTD.

SPECIFICATION FOR COTCO LED LAMP

Document No: SPE/LC503AYL2-30P-A
Model No : LC503AYL2-30P-A
Rev. No: 04
Date: 2006-03-24


Description:

30 Degree 5mm Round LED Lamp in
Amber Color with White Diffused Lens and
Stopper

Dice Material: AlGaInP

Confirmed
by Customer: _____

Date: _____



Applications:

- Advertising Signs
- Indicators
- Traffic
- Automotive Lighting

Absolute Maximum Ratings at Ta = 25°C

Items	Symbol	Absolute maximum Rating	Unit
Forward Current ^{*2}	I _F	50	mA
Peak Forward Current ^{*1}	I _{FP}	200	mA
Reverse Voltage	V _R	5	V
Power Dissipation	P _D	130	mW
Operation Temperature	T _{opr}	-40 ~ + 95	°C
Storage Temperature	T _{stg}	-40 ~ +100	°C
Lead Soldering Temperature	T _{sol}	Max.260°C for 3 sec Max. (3mm from the base of the epoxy bulb)	
Electrostatic Discharge Classification (MIL-STD-883E)	ESD	Class 1	


*1 pulse width ≤ 0.1 msec duty $\leq 1/10$

*2 For long term performance the drive currents between 10mA and 30mA are recommended. Please contact COTCO sales representative for more information on recommended drive conditions.

Typical Electrical & Optical Characteristics (Ta = 25°C)

Items	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F = 20\text{mA}$	---	2.1	2.6	V
Reverse Current	I_R	$V_R = 5\text{V}$	---	---	100	μA
Dominant Wavelength	λ_D	$I_F = 20\text{mA}$	584	591	596	nm
Luminous Intensity	I_V	$I_F = 20\text{mA}$	3000	4500	---	mcd
50% Power Angle	$2\theta_{\frac{1}{2}\text{H-H}}$	$I_F = 20\text{mA}$	---	30	---	deg

Dimension Drawing




Standard bins for LC503AYL2-30P-A ($I_F = 20\text{mA}$):

Lamps are sorted to Luminous Intensity – I_V & Dominant Wavelength – λ_D bins shown.

Orders for LC503AYL2-30P-A may be filled with any or all bins contained as below.

All Luminous Intensity – I_V & Dominant Wavelength – λ_D values shown and specified are at $I_F=20\text{mA}$.

* **W+**



* W+ indicates Luminous Intensity is at W bin or above.

Important Notes:

- 1) All ranks will be included per delivery, rank ratio will be based on the Dices distribution.
- 2) Pb content <1000PPM.
- 3) Tolerance of measurement of luminous intensity is $\pm 15\%$.
- 4) Tolerance of measurement of dominant wavelength is $\pm 1\text{nm}$.
- 5) Tolerance of measurement of V_f is $\pm 0.05\text{ V}$.
- 6) Packaging methods are available for selection, Please refer to PACKAGING STANDARD.
- 7) Please refer to LED LAMP RELIABILITY TEST STANDARD for reliability test conditions.
- 8) Please refer to APPLICATION NOTES for Application.

Graphs




FIG.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




FIG.2 REVERSE CURRENT VS. REVERSE VOLTAGE.




FIG.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT.




FIG.4 RELATIVE LUMINOUS INTENSITY VS. WAVELENGTH.




FIG.5 MAXIMUM FORWARD DC CURRENT VS AMBIENT TEMPERATURE ($T_{jmax}=105^{\circ}\text{C}$)




FIG.6 FAR FIELD PATTERN

Items	Signatures	Date
Prepared by	LiuZM	2006-03-24
Checked by	Aldosin	2006-03-24
Approved by	David	2006-03-24
FCN#	FCN20060077	

Revision History		
Rev. No	Date	Change Description
B	31May04	Change IV, VF & λ_D Rank form.
C	04Aug04	Add Notes. Change FIG.1&3&5
04	2006-03-24	Cancel VF bin.

Data is subject to change without prior notice; please refer to COTCO Website for the latest version.

Copyright©2002 Cotco International Ltd.