


Constant current LED power supply 80W

- 160-264VAC input range
- Small in size, light in weight, highest efficient
- Protection function: short circuit/overload/over temperature
- Cooling by free air convection
- Waterproof degree: IP67
- 100% full load built-in testing
- 2 years warranty



LPA-80W				
Model		LPA-80-2800	LPA-80-2100	LPA-80-1400
OUTPUT	Rated Current	2800mA	2100mA	1400mA
	DC output voltage	16~28V	25~38V	35~57V
	Rated power	78.4W	79.8W	79.8W
	Ripple&noise	200mvp-p	200mvp-p	200mvp-p
	Voltage accurate	±5%	±5%	±5%
	Load adjusting rate	±2%	±2%	±2%
INPUT	Input voltage range	170~260VAC, 238~370VDC		
	Frequency	47~63Hz		
	AC input current	1.1A/230VAC		
	Efficiency	85%		
	Inrush current	cold start current 50A/230VAC		
PROTECTION	Leakage current	<0.5mA/240VAC		
	Overload protection	±5% rated current limit		
		Protection type: rated current limit		
	Overtemperature protection	Shell temp ≥ 105°C, start over temperature protection		
Protection mode: cutoff output, auto-recovery after temperature				
ENVIRONMENT	Working	-10°C~+60°C, 20%~90%RH		
	Storage	- 20°C~+85°C, 10%~95%RH non condensing		
	Withstand vibration	10~500HZ, 2G 10min/ period for 60minutes, each axes		
SAFETY	Withstand voltage	I/P-O/P: 1.5KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC		
	Isolated resistance	I/P-O/P、I/P-FG、O/P-FG: 100M ohms/500VDC		
FITSTANDARDS	Safety standards	Fit UL1012, IP67 protect level		
	EMC standards	meet EN55022, CLASSB		
OTHER	Size	185*69*43mm (L*W*H)		
	Weight/ packing	0.9kg/20pcs/19kg/0.026m³/1.15CUFT		
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and			
	2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire			
	3. Tolerance : includes set up tolerance, line regulation and load regulation.			