

LED constant voltage waterproof switching power supply 200W

Features:

- Constant voltage style power supply
- 170~264VAC AC input
- Small volume, low weight, high efficiency
- Protections: short circuit/over load/over voltage/over temp
- Cooling by free air convection
- Fully encapsulated with IP67 level
- 100% full load burn-in test
- 2Year warranty



LPV-200W				
Model		LPV-200-12	LPV-200-24	LPV-200-36
OUTPUT	DC voltage	12V	24V	36V
	Voltage tolerance	±1%	±1%	±1%
	Rated current	16.5A	8.3A	5.5A
	Current range	0~16.5A	0~8.3A	0~5.5A
	Rated power	198W	199.2W	198W
	Ripple&noise	150mvp-p	200mvp-p	200mvp-p
INPUT	Voltage range	180~264VAC, 255~373VDC		
	Frequency	47~63Hz		
	AC current	2.5A/230VAC		
	Efficiency	82%	84%	84%
	Inrush current	Cold start current 40A/230VAC		
PROTECTION	Leakage current	<2.5mA/240VAC		
	Over load	Rated output power 105%~135%start over load protection		
		Protection type: hiccup mode, auto-recovery after fault condition is removed		
	Over voltage	15.6~17.8V	30.6~33.2V	42.6~44.2V
		Protection type: hiccup mode, auto-recovery after fault condition is removed		
Over temperature	Shell temp≥85℃, start over temperature protection			
ENVIRONMENT	Working temp,humidity	-10℃~+60℃, 20%~90%RH		
	Storage temp,humidity	-20℃~+85℃, 10%~95%RH non condensing		
	Withstand vibration	10~500HZ, 2G 10min/1cycle, period for 60minutes, each		
SAFETY	Withstand voltage	I/P-O/P: 1.5KVAC I/P-FG: 1.5KVAC O/P-FG: 0.5KVAC		
	Isolated resistance	I/P-O/P、I/P-FG、O/P-FG: 100M ohms/500VDC		
FITSTANDARDS	Safety standard	Fit UL1012, IP67 protect level		
	EMC standard	Fit EN55022, CLASSA		
OTHERS	Dimension	240*69*43mm (L*W*H)		
	Weight/packing	1.26kg/20pcs/26kg/0.033 m³/1.15CUFT		
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25℃ of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation.			